

# A290PSE Hand Dryer

## AUTOMATIC – No. HD15364



Upper Cover - Metallic Silver  
Lower Cover - Grey



### FEATURES

Dry Time Indicator - LED displays to user optimum dry time.  
Fully automatic infra-red operation.  
Low power, uses less electricity.  
Compact size – smaller than other dryers.  
Safety – Over temperature cut off, blower shut down after 60 seconds.  
Snap in motor assembly

### SPECIFICATIONS

Construction: All plastics are flame retardant to UL94 V0. Class II double insulated, enclosure splash/drip proof to IPX3, non-corrosive.  
Gross weight: 2.3kgs. Shipping weight 2.5kgs.  
Colour: Upper Cover - Silver. Lower Cover - Grey  
Electrical: 220-240 V~ 50-60Hz, 1.71 kW, 7.4 AMP, 120V15 AMP.  
Noise level: 69 dB. Air velocity 25m/s.

### PRODUCT SIZE

Height - 220 mm  
Width - 210 mm  
Depth - 163 mm

### PLANNING

Generally, one hand dryer is recommended for every two hand basins. For heavy use in large washrooms, use two hand dryers for every three basins. Install hand dryers adjacent to wash basins, out of the way of projecting storage cabinets or other objects to optimise access and movement around the dryer. In congested areas, site dryers to ensure good traffic flow between wash basins and dryers. If more than one is used, dryers should be placed at least 500mm to 600mm apart.

### ELECTRICAL SAFETY APPROVALS

AS3304, AS3300, NZ6362, NZ6300, IEC335-2-23:1996, IEC 335-1:1991 incl Amend 1, EN55014, EN50082-1, EN60555-2/3, International CB Text Certificate No. AU0182, Certificate of suitability (Australia) No. Q070141

### ELECTRICAL CONNECTION & ADDITIONAL NOTES

Installation and servicing should be carried out by a qualified person. Fixed wiring is recommended for all installations. Wiring should emerge from the wall at the position marked fixed wiring & supply cord entry. All wiring, related switches and circuit protection must be installed in accordance with local electrical wiring regulations and codes. This unit is double insulated and does not require earthing/grounding.

### RECOMMENDED MOUNTING HEIGHTS

From the floor to the bottom of the dryer:  
Men's washrooms - 1200mm.  
Women's washrooms - 1150mm.  
Children's washrooms ages up to 10 - 860mm.  
Children's washrooms ages up to 16 - 1120mm.  
Disabled person's washrooms - 1015mm.

### TOTAL SATISFACTION WARRANTY

Warranty: 3 years. Dryers requiring attention or repair within the warranty period should be returned to Service Centre:  
Ardrich Limited, 31 Hannigan Drive, Auckland 1072.  
Call 0800 802861 for replacement parts.

DISABLED PERSON COMPLIANT

EMC COMPLIANT

Designed and Manufactured in New Zealand



### ARDRICH LIMITED

Phone 0800 802 861 095702861  
Fax 095702864  
Email sales@ardrich.co.nz

